

IN THE DRAWINGS

The drawings have been corrected to place them in formal acceptable form, and to provide reference characters and numerals. The corrected drawings are submitted herewith as Appendix 3.

REMARKS

Favorable reconsideration of this application in light of the following discussion is respectfully requested.

Responsive to the Office Action of October 4, 2006, Applicant's newly appointed Counsel submits the following. The Specification has been amended to place it in a more acceptable format and to correct clerical errors of form, text and punctuation. Applicant's newly appointed Counsel has exercised due care in amending the specification to not add (or delete) any text that could be construed to be new matter. A clean substitute Specification copy, and the required "marked-up" copy, are submitted herewith.

The drawings have been corrected to place them in formal acceptable form, and to provide reference characters and numerals. The corrected drawings are submitted herewith.

Claims 48-59 and 61-67 have been cancelled without prejudice, and without admission of anticipation, in favor of newly added Claims 68-73, which more clearly define the essence of Applicant's invention. Thus, the rejection made under 35 USC 112 should be withdrawn.

An appropriate Petition for Extension of Time of one month, to extend the response time until February 4, 2007, is also submitted herewith.

The Examiner's primary reference of rejection, in the outstanding Office Action, is Simpson U.S. Pat. No. 5,999,882. Applicant and her Counsel have carefully reviewed this Simpson disclosure and submit that it solely pertains to the provision of weather information to aviation or transportation professionals, along a travel route or flight plan. The client system 14 of Simpson does disclose in Col. 8, lines 13-15 that "the client system may be a portable laptop computer . . .", after disclosing in its previous disclosure that the client system 14, and the server system 12 may be implemented using virtually any type of computer. See

Col. 5, lines 3-5. The server system 12 may be remote from client system 14 (on board the transportation vehicle) and obtains weather data over communication links 18, see FIG. 1; and, the client system 14 operates with the server system to receive weather data from links 18. Also see Col. 6, line 4-9, which appear to indicate that the scope of the Simpson invention may comprise additional or different types of weather information, which disclosure contains no mention or suggestion of other types or kinds of information data. Summarily, Simpson only utilizes flight plan or travel route data and weather data.

We now direct the attention of the Examiner to newly added independent method Claim 68 which is as follows:

68. (new) A method of providing an electronic flight bag to and for use by an aircraft aviation professional, comprising:
- (a) providing a transportable computer to be carried by said aviation professional to and from and within an aircraft and airport;
 - (b) programming said computer with linear and non-linear algorithms and operating programs capable of: processing flight information, manipulating flight related data in a non-linear algorithm thereby aiding in flight decision-making processes resulting in solutions to flight related mathematical computations and runway selections and aircraft operating parameters and procedures, calculating pilot fatigue limits and scheduling issues and fuel computations, providing data displays to said professionals; and
 - (c) loading aircraft and flight related data into said computer and pertaining to a flight plan, weather information for said flight plan, aircraft crew scheduling, aircraft maintenance information, aircraft load weight and balance, and flight passenger concerns.

This new Claim 68 defines applicant's novel method of providing for an aviation professional a lightweight and easily manipulated / handled electronic flight kit bag to replace the standard very heavy and cumbersome kit bag pilots and other transportation professions routinely carry to and from and within aircrafts and airports. The provided transportable laptop computer is properly programmed and data loaded with all necessary programs and aircraft flight information and procedures to assist and support the professional's flight operations and decisions. Various relevant types of flight and aircraft related data are loaded


into the laptop, not just flight plan and weather information as disclosed in Simpson. In fact, the Simpson reference is devoid of any disclosures, suggestions or inference of an electronic flight (or travel) kit bag system or method, as claimed in new Claim 68.

Accordingly, new independent Claim 68 and its dependent Claims 69-73 are clearly allowable over the Simpson '882 U.S. reference, which taken alone, or even in combination with the other references cited by applied by the Examiner, does not anticipate or make obvious Applicant's invention method as clearly defined in newly submitted Claims 68-73.

Consequently, in view of the present amendment, no further issues are believed to be outstanding in the present application, and the present application is believed to be in condition for formal Allowance. A Notice of Allowance for Claims 68-73 is earnestly solicited.

Should the Examiner deem that any further action is necessary to place this application in even better form for allowance, the Examiner is encouraged to contact Applicant's undersigned representative at the below listed telephone number.

Respectfully submitted,
MAIER & MAIER, PLLC

A handwritten signature in black ink, appearing to read 'Timothy J. Maier', written in a cursive style.

Timothy J. Maier
Reg. No. 51,986

Tel. (703) 740-8322
Fax (703) 991-7071
TJM

Appendix 1 – Clean version of Amended Specification
Appendix 2 – Marked-up copy of Amended Specification
Appendix 3 – Corrected Drawings

SUMMARY OF THE INVENTION
FIELD

[0001] This invention relates in general to computers, and, in particular, to the processing and translating of transportation data and functions through linear and non-linear methodologies into active operating parameters.

BACKGROUND OF THE INVENTION

BACKGROUND

[0002] The historical development of this invention, the EKB, can be examined from three general perspectives: (1) weight[[],]; (2) utility[[],]; and (3) function.

1. KIT BAG WEIGHT

[0003] ~~1) Kit bag weight:~~ Pilots, and other transportation professionals, routinely carry extremely heavy bags, full of paraphernalia specific to their art, including maps, calculators, logs, charts, navigation instruments, and so on. This bag is usually referred to as a "kit bag" and generally, for an aviation professional, for example, weights between 30 and 80 pounds. According to FAA Medical and Workman's Compensation statistics, the most common loss of work time, on the job injuries, in this work group are related to moving, carry and stowing the "kit bag": torn shoulder ligaments, dislocated elbows, "slipped disk" back problems, and knee-joints joint problems.

[0004] The problem of the heavy kit bag/injured pilot has been attempted to be solved by at least one other means, adding wheels and a handle to the kit bag, roller-suitcase style.

[0005] The following invention was originally conceived with the intention of simply solving the ~~weigh~~ weight problem, as the entire contents of a traditional kit bag can be reduced to an electronic equivalent of about 3-7 lbs. However, in developing the project, other innovative and highly functional properties became apparent.

2. UTILITY

[0006] ~~2) Utility:~~ The current kit bag can be compared to a cumbersome sideways drawer. An area is generally left in the cockpit, to the right or left of the pilot, where the kit bag can be placed. In flight, if an item is needed from the kit bag, there often ensues an unpacking, rummaging and hunting expedition into the kit bag for the sought after manual, tool, chart, log or other desired item. The pilot is taken out of the flying-loop while this hunting expedition is in progress. Another draw-back of the old-fashioned kit bag is the traditional coffee-spill. Coffee-cup holders in the cockpit are generally placed right above the kit back stowage compartment. A kit bag is not considered "broken in" until at least one cup of coffee, orange juice or other non-paper friendly liquid has spilled into the contents of the kit bag and ruined the most important documents needed for the flight in progress, as well as any other important paperwork contained therein.

[0007] Further, the traditional kit bag must be hauled around like an additional suitcase. It is here that most on-the-job injuries occur: removing the kitbag from too tight of a storage area, heaving it into overhead bins, lifting it in and out of vans and storage facilities.

[0008] The utility problem has heretofore not been successfully addressed. Although, traditionally kit bags are made in various shapes and from various sorts of

materials (including tin, plastic-covered card-board, canvas, etc.), they all only serve to hold contents in a standard method with the result being bulky, cumbersome and heavy.

[0009] The EKB approaches the problem from another perspective. By changing the contents of the kit bag, the nature of the exterior of the "bag" is also modified. The E6-B slide rule is a device, for instance, which can eliminate some wind charts and solve some airspeed/ground speed calculations. ~~Its predecessor, the~~ The handheld calculator, designed for the same function, was an electronic advancement, as is the Performance Management System, an integrated on-board aircraft system. Although these devices may individually partially contribute to certain aspects of a ~~kit-bags~~ bag's contents and function (~~see #3 following~~ See Section 3 below), none address the concept of deleting the load or form of the kit bag in any way, let alone the entirety of all functional aspects of a kit bag. The EKB is light weight and easily manipulated. It can be moved without undue stress, strain or physical contortion. In use, it will not be below the coffee holders! Less physical storage place is needed, resulting in more cockpit room. Also, less weight is carried on-board, resulting in substantial and measurable fuel savings.

3. FUNCTION

[0010] ~~3) Function:~~ As mentioned, with the traditional kit bag, the pilot must rummage through the contents in search of the needed material(s), taking the pilot out of the immediate operating loop, and costing precious time, especially in an emergency. Often needed particulars are located in separate and disparate areas. The pilot may

need to consult one manual for operating parameters, another book of charts for an off-line emergency airport, another manual for the emergency procedure, while simultaneously talking with dispatch or operations on a radio. The other pilot (in generally two-person airline crew) is left alone to fly a possibly crippled airplane, talk to the flight attendants and passengers, and negotiate with air-traffic control.

[0011] Few attempts have been made to alleviate the duress caused by this plethora of unrelated information presented in physically unrelated forms. One limited suggestion known to this inventor was an on-board type computer which used an aircraft up-link device to managed charts. This failed FAA certification, however, partly because it relied on aircraft power. The EKB, while providing much more information as well as information processing, relies on internal battery power (although it can be "charged" from aircraft power as well). The FAA has provided, incidentally, provisional operating permission for use of the EKB on-board.

[0012] The EKB requires learning only simple key-stroke patterns to be a superior replacement for the traditional kit bag and contents in many operating situations. Optimal functionality is acquired when all mentioned inputs are interfaced and electronically "evaluated." Several steps can be incorporated in one or a few input strokes from a proficient operator.

[0013] Additionally, the EKB has the potential capability to actually "fly" the aircraft within certain parameters to a touch-down and landing.

[0014] A major improvement over the traditional "kit bag" is that the computerized version can manipulate data in a non-linear algorithm, aggregating and sorting choices, thereby aiding in decision-making processes resulting in solutions to mathematical

computations, runway selection, operating parameters, figuring pilot fatigue limits and scheduling issues. Output solutions can be interfaced with the craft, auto-pilot style, so that a craft could be manipulated through the EKB via radio/satellite/other mode transmissions by a ground operator in certain emergencies, such as crew incapacitation.

OBJECTIVES

[0015] It is the principal object of the current invention to create a device which, through the amalgamation and formalization of disparate operating data into a functional methodology that can then translated quickly and easily into today's operating environment, will not only make a pilot's overburdened job easier, but save lives.

RELATED ART

[0016] In order to provide background information so that the invention may be completely understood and appreciated in its proper context, reference is made to a number of prior art patents and publications as follows:

- computers
- calculating devices
- radios
- printers
- autopilots
- radio-controlled aircraft/missiles

_____Whatever the precise merits, features and advantages of the above cited references, none of them achieve or fulfills the purposes of the present invention.

SUMMARY OF THE INVENTION

SUMMARY

[0017] Other than through exterior suit-case like changes, organizing the contents of the standard pilot kit bag into a more manageable, user[[/]]_friendly format has not been attempted. Coalescing and analyzing kit bag data electronically is a modern and sensible solution to the both the problems of physical ungainliness and practical application of the standard kit bag. Additionally, the problem of aircraft control during pilot incapacitation has also been inadequately addressed by any means other than self-help (oxygen use) or on-board autopilot capabilities. Heretofore there has been no device which offers a simultaneous, practical and coherent solution for either problem. The electronic, computerized portable kit bag (EKB), offers solutions to both problems in a single package.

[0018] The present invention is a portable, computerized, electronic kit bag (EKB) consisting of standard and state-of-the-art computer parts and peripherals, interfaced for maximum utility. The EKB has a central operating program which assesses the relationships of input data through a three-dimensional logic based decision-making algorithm and has output formatted to be utilized either directly by the end user, an intermediate user, by a user through an aircraft system, or directly from the device to an aircraft system or autopilot.

BRIEF DESCRIPTION OF THE DRAWINGS

BRIEF DESCRIPTION OF THE FIGURES

[0019] Advantages of embodiments of the present invention will be apparent from the following detailed description of the exemplary embodiments thereof, which description should be considered in conjunction with the accompanying drawings in which:

[0020] Fig. 1 ~~The Basic EKB, sample solution and construction, exterior view is a front exterior view of an exemplary laptop-style EKB.~~

[0021] Fig. 2 ~~All in one interactive headgear, sample interface, user friendly output data acquisition is a front exterior view of an exemplary "all-in-one" interactive headgear EKB interface.~~

[0022] Fig. 3 ~~Additional ergonomic design, EKB alternative construction, exterior view is an exterior view of an exemplary ergonomically-designed EKB attached to the leg of a user.~~

[0023] Fig. 4 ~~Current standard, internal data processing flow diagram is an exemplary diagram showing an exemplary prior art decision-making process.~~

[0024] Fig. 5 ~~Improvement # 1, internal data processing flow diagram is an exemplary diagram showing a matrix decision-making process for use by a transportation professional according to an exemplary embodiment.~~

[0025] Fig. 6 ~~Improvement #2, internal data processing flow diagram is an exemplary diagram showing a three-dimensional decision-making process for use by a transportation professional according to another exemplary embodiment.~~

[0026] Fig. 7 ~~Potential application, input EKB output processing sample~~ is an exemplary diagram depicting a potential application of an EKB as part of a system for active control of an operating transportation craft.

DETAILED DESCRIPTION OF THE INVENTION

DETAILED DESCRIPTION

[0027] Aspects of the invention are disclosed in the following description and related drawings directed to specific embodiments of the invention. Alternate embodiments may be devised without departing from the spirit or the scope of the invention. Additionally, well-known elements of exemplary embodiments of the invention will not be described in detail or will be omitted so as not to obscure the relevant details of the invention.

[0028] The EKB requires learning only simple key-stroke patterns to be a superior replacement for the traditional kit bag and contents in many operating situations. Optimal functionality is acquired when all mentioned inputs are interfaced and electronically "evaluated." Several steps can be incorporated in one or a few input strokes from a proficient operator. Additionally, the EKB has the potential capability to actually "fly" the aircraft within certain parameters to a touch-down and landing.

[0029] A major improvement over the traditional "kit bag" is that the computerized version can manipulate data in a non-linear algorithm, aggregating and sorting choices, thereby aiding in decision-making processes resulting in solutions to mathematical computations, runway selection, operating parameters, figuring pilot fatigue limits and scheduling issues. Output solutions can be interfaced with the craft, auto-pilot style, so

that a craft could be manipulated through the EKB via radio/satellite/other mode transmissions by a ground operator in certain emergencies, such as crew incapacitation.

[0030] The portable, computerized electronic kit bag (EKB) consists of standard and state-of-the-art computer parts and peripherals, interfaced for maximum utility. The EKB can be constructed similarly for several end user[[-]]/operators, including captains, pilots, commanders, drivers, dispatchers and operations personnel of boats/ships, automobiles, aircraft, spacecraft and other transportation devices. The example used here will apply to the pilot of an airliner.

[0031] The computer itself is a laptop type, or ergonomic variation thereof, such as a knee-top style (Fig. 3). Enhancements include a translucent secondary window designed for the purpose of overlaying "heads-up" display information directly over maps, charts or other data displayed by a primary computer screen-- (Fig. 1). Peripherals include printers, zip-drives, and other standard or non-standard computer devices. The all-in-one interactive headgear which interfaces with an EKB (Fig. 2), is a sample non-standard peripheral.

[0032] Input is acquired online or off-line through modem, cable, direct input, CD, DVD, floppy disk, voice recognition, infra red, radio (UHF, VHF), computer linking, video, digitally, scanning or any accessible and/or compatible means, internet and intranet systems included.

[0033] The nature of input data and sources can be typical and/or operationally unusual. This "parent" system is linked with other extant operating systems and data bases, such as reservations, meteorological, dispatch (routing, diversion and alternate

planning), load planning, scheduling, airplane operating parameters, aircraft instruments and related systems (engine, hydraulic, GPS, inertial, radar, GPWS, collision avoidance, etc.), FAA crew rest and duty limits, union regulations and rules, charts/maps, log-books, airport analyses and any and all other links and data that may be made available to computer acquisition.

[0034] Input is manipulated internally and integrated through traditional linear, "matrix," or multi-level, cross-access "textotrix" methodology (described below). ~~The In the embodiment depicted in Fig. 6 the central operating program assesses the relationships of input data through a three-dimensional logic based decision-making algorithm. (Fig. 4,5,6), providing Figs. 4, 5 and 6 provide the user with up-to-the-minute, operating information available for pre-flight, en route, post flight or future operations. The pilot can access incremental feedback, monitor, or make adjustments at any point. Processing includes recording, coping, filing, updating, organizing, printing, and generating data, literature, schedules, routing, planning, computations and permutations of all phases of the flight needed at any given point in time.~~

[0035] The processing algorithm operates as follows (for example): a unit of data, or calculation, is presented as input (the wind is 240/10) the result can be accessed immediately, (suggested runway at ORD is 22) or modified by adding another unit of data, or calculation (ice accumulating rapidly) with the result again capable of being accessed, (runway 32 longer, suggested better choice, in spite of wind) or modified (crew legality reaching hourly limit) results available, (runway 27 adequate, quicker access, legal compromise) or modifiable . . . (left wing heat becomes

inoperative) and so on. See Fig. 6 for how the system can “think” and interpolate unrelated data sources.

[0036] Process information is presented as factual output usable to determine operating options: formula calculations to aid in decision-making and suggested “best choice” solutions.

[0037] Output solutions can include flight planning, en route decision making moderated by weather and operating factors, financial analyses of integrated choices, fuel computations, weight-and-balance, crew planning, passenger accommodation/satisfaction result prognostication, and statistics relating to associated elements of an on-time/safe flight/travel operation, and so on.

[0038] Output can be presented directly or indirectly, electronically, graphically, printed or displayed on the system screen, or through associated systems by way of cable, infra-red, printer, modem, wireless or any other compatible or available transfer output transfer system.

[0039] The EKB data output is formatted to be utilized either directly by the end user, an intermediate user, by a user through an aircraft system, or directly from the device to an aircraft system or autopilot. The EKB includes the capability of being interfaced directly with the aircraft, auto-pilot style, through “hard-wired” cable (by plugging a unit connector cable directly into the autopilot or specific system computer bay), cable-free infrared (for systems so modified to assure compatibility), electronic or other information exchange systems. The Fig. 7 is an exemplary diagram of the process defined by the transmittal of data from a ground-based operator system Ground Based Operator System 702, through an on-board combined-functions device in

Operating Transportation Craft 700, resulting in the manipulation or active control of an ~~operating transportation craft~~ Operating Transportation Craft 700 that can be established in the following manner: ~~the EKB~~ an EKB interfaced with Operating Transportation Craft 700 includes receptivity to input in the form of voice activated commands or electronic data transfer from either Ground Operators 702 or Satellite 704 solely or in conjunction, and can output directly to aircraft control systems. Thus, functional radio control of the aircraft can be established from ground based personnel or equipment in emergency situations, such as pilot incapacitation.

[0040] Fig. 4 shows a current standard for a linear (i.e. one dimensional) decision-making process used by a transportation professional such as a pilot. The pilot-Pilot 400 receives information as Input 402 from flight operations regarding a flight plan which includes departure point, destination, alternate airports, and fuel time. The pilot-Pilot 400 then reviews and uses the information leading to Output 414; Then the pilot-then Pilot 400 acquires a weather briefing as Input 404. Then that information is used by the pilot-Pilot 400 leading to Output 414; Then the pilot-then Pilot 400 acquires, referring to #3 and said figure, information about cruise-crew scheduling and other limitations regarding the time the crew has been on duty for this particular mission as Input 406. Additionally, the pilot-Pilot 400 acquires maintenance information about the plane from the log book on the airplane, from pilot briefings and/or from the mechanics as Input 408. Additionally, information as Input 412 is obtained about passenger concerns, e.g. particular passenger information as well as the passenger manifest and information as Input 410 about the cargo, e.g., types of cargo, restricted items,

livestock, etc. With this information, as it comes incrementally and linearly to the pilot ~~Pilot 400~~, the pilot Pilot 400 makes modified decisions about the flight as Output 414.

[0041] ~~Referring to fig. 5~~ Fig. 5, improvement No. 1, is a diagram showing a matrix (i.e. two-dimensional) decision-making process for use by a transportation professional such as a pilot. ~~when the information~~ Information such as Input 502 is acquired by the pilot ~~Pilot 500~~, as the additional information such as Input 504 is given to the pilot ~~Pilot 500~~, the prior information learned from Input 502 by the pilot ~~Pilot 500~~ is used in supplying the next new information from Input 504 to the pilot ~~Pilot 500~~. So that, for example, the first linear information received as Input 502 by the pilot ~~Pilot 500~~ would be the flight operations in this example, before the next information from Input 504 is given to the pilot ~~Pilot 500~~, the weather information from Input 504 given to the pilot ~~Pilot 500~~ is adjusted (e.g., Input 504 is modified by an EKB rendering calculations) based on the flight operation from Input 502 so that the pilot ~~Pilot 500~~ can either access the information directly as Input 502, e.g., from flight operations, or he can access the weather information from Input 504 so that the flight plan from Input 502 is modified by the influence of the weather information. Likewise, when the third element is added as Input 506, for example, crew limits, when that information is fed to the pilot ~~Pilot 500~~, it an EKB can modify or suggest a flight plan to be within the limits of the crew.

Specifically, this improvement No. 1 ensures that the crew limits from Input 506 will be taken into consideration notwithstanding whether the pilot ~~Pilot 500~~ was thinking about that particular limitation or any of the other limitations or data being fed to him. The program figures the limits based on the flight operations plan from Input 502 in the particular circumstances. For example, there are different limits based on whether the

flight is domestic or international. Specifically, a crew may only have a certain amount of time left on that leg of the trip which may be shorter than the flight mission which could present a problem to ~~the pilot~~ Pilot 500. This improvement No. 1 takes into consideration the crew limits from Input 506 whether or not ~~the pilot~~ Pilot 500 actually considered the same and this way the improvement No. 1, flight operations plan from Input 502 is adjusted according to the weather from Input 504, the crew limits from Input 506, the maintenance from Input 508, the load from Input 510 and the passengers from Input 512. Another example is for the load from Input 510. The final weight and load of the plane and passenger quantity under some circumstances is figured out by ~~the~~ a pilot especially including variables such as fuel, weather and destination. Under this improvement No. 1 system, for example, if at the time of take off it was starting to rain and it was necessary for ~~the pilot~~ Pilot 500 to figure out a new runway length as Output 514, all these calculations can be done by the computer and assessed in real time leading to Output 514 as opposed to having ~~the pilot~~ Pilot 500 have to research his individual paper manuals as it is presently done for new factors in view of the rain in regards to, for example, take off length, runway length, speed of the airplane under moisture conditions and other adverse conditions. Improvement #1 cumulative adds step by step information, modifying the result mechanically as needed. ~~Referring to Fig. 6, improvement #2 the computer generally returns to the beginning step and reassesses all factors based on all present facts this system knows, such that the points of analysis by the system for use by the pilot is re-analyzed with the newest input and output that occurs at any point along the way. In this situation, the pilot can (Option 1) review the information and make a decision, (Option 2) allow the computer to solve some of the~~

~~questions and base decisions on personal knowledge and the information provided by the computer, or (Option 3) allow the computer to control and make the decisions. The use of the term "textotrix" [L. *texus*, to weave, seen also in *texture*, *textile*, *context* and L. *-trix*, as in *matrix*] is that of the inventor, an array of elements in row, columns and stacks, treated as a unit using special algebraic laws in facilitating the study of relations between elements, used herein reference to the processing of information in three dimensional levels.~~

[0042] Fig. 6, improvement #2, is a diagram showing a textotrix (i.e. three-dimensional) decision-making process for use by a transportation professional such as a pilot, wherein the point of analysis/re-analysis of input/output can occur at any point. Computer System 616 generally returns to the beginning step and reassesses all factors based on all present factors from Inputs 602, 604, 606, 608, 610 and/or 612 that System 616 knows, such that the points of analysis made by System 616 for use by Pilot 600 is re-analyzed with the newest input and output that occurs at any point along the way. In this situation, Pilot can (Option 1) review the information and make a decision as Output 614, (Option 2) allow the computer to solve some of the questions and base decisions leading to Output 624 on personal knowledge and the information provided by the computer, or (Option 3) allow the computer to control and make the decisions as Output 634.

[0043] The use of the term "textotrix" (L. *texus*, to weave, seen also in *texture*, *textile*, *context* and L. *-trix*, as in *matrix*) is that of the inventor, meaning an array of elements in rows, columns and stacks, treated as a unit using special algebraic laws in

facilitating the study of relations between elements, used herein in reference to the processing of information in three dimensional levels.

[0044] In Summary, the present invention is a portable, computerized, electronic kit bag (EKB) consisting of standard and state-of-the-art computer parts and peripherals, interfaced for maximum utility, a central operating program[[]] which assesses the relationships of input data through a three-dimensional logic based decision-making algorithm, an EKB data output formatted to be utilized either directly by the end user, an intermediate user, by a user through an aircraft system, or directly from the device to an aircraft system or autopilot[[,]]. ~~a~~ A process defined by the transmittal of data from a ground based operator or system, through an on-board combined-functions device, resulting in the manipulation or active control of an operating transportation craft[[,]]. Also an EKB may have a translucent secondary window designed for the purpose of overlaying "heads-up" display information directly over maps, charts or other data displayed by a primary computer screen[[,]]; and an all-in-one interactive headgear interfaces with an EKB[[,]]. ~~and~~ Optionally an EKB may be in the form of an ergonomically designed knee-top style EKB.

[0045] The following discussion is a working example allowing a user, practicing at least one embodiment of the invention, to organize and manipulate disparate data and functions, and may consist of, *inter alia*, the following steps:

(a) the electronic computational device is started;

(b) the user selects the browser function;

(c) the user selects from amongst a series of icons with linking capability to, for example, a connection function, a search function, a tools function, a programs function, or a control function;

(d) the user selects an option from the browser, in this embodiment, SEARCH FUNCTION, and opens the program;

(e) data is inputted into the search function by the user, in this embodiment, ENGINE OUT;

(d) a list is presented with hyperlinked options, in this embodiment, AIRSPEEDS, ALTERNATE AIRPORTS, CHECKLISTS, LANDING WEIGHTS, REPORTS;

(g) the user selects an option, in this embodiment, ALTERNATE AIRPORTS;

(h) a list of alternate airports is displayed;

(i) the user selects an alternate airport;

(j) the data about that airport is displayed with additional links to related topics and functions, in this embodiment, CALCULATE TIME TO AIRPORT, CALCULATE FUEL TO THE AIRPORT; and

(k) the user continues with the search tree, selecting another option or returns to the main menu, depending on the program and search function in use; alternatively,

(l) when the user wants to make a calculation, data is inputted into the search function by the user, for example, ENGINE OUT;

(m) a list is presented with hyperlinked options, in this embodiment, AIRSPEEDS, ALTERNATE AIRPORTS, CHECKLISTS, LANDING WEIGHTS, REPORTS;

(n) the user selects an option, for instance, AIRSPEEDS;

(o) a list is presented, in this embodiment, LANDING and GO-AROUND;

(p) the user makes a selection, such as LANDING;

(q) a list is presented of airspeed/landing functions, in this embodiment,

REFERENCE SPEEDS;

(r) the user selects the desired function and inputs the prompted data, in this embodiment, WET/DRY;

(s) the user continues to input prompted data, in this embodiment, WIND

COMPONENT; and

(t) the system calculates and outputs the needed airspeed;

(u) the user may continue the search tree, select another option, or return to the main menu, depending on the program and search function in us; alternatively,

(v) when the user wants to make a decision, data is inputted into the search function by the user, in this embodiment, ENGINE OUT;

(w) a list is presented with hyperlinked options, in this embodiment: AIRSPEEDS, ALTERNATE AIRPORTS, CHECKLISTS, LANDING WEIGHTS, REPORTS;

(x) the user selects an option, in the current embodiment, LANDING WEIGHTS;

(y) a list is presented, in the current embodiment, CURRENT WEIGHT and CALCULATED WEIGHT;

(z) data is outputted, in this example, LANDING WEIGHT IS 500,000 POUNDS, TOO HEAVY, DUMP FUEL;

(a') the user is presented a decision-making option; alternatively,

(b') when a user wants to make a report, data is inputted into the search function by the user, in this example, ENGINE OUT;

(c'), a list is presented with hyperlinked options, in this example, AIRSPEEDS, ALTERNATE AIRPORTS, CHECKLISTS, LANDING WEIGHTS, REPORTS;

(d') the user selects an option, continuing the search string, REPORTS;

(e') a list is presented containing, in this example, ATC, COMPANY, OTHER AIRCRAFT;

(f') the user makes a selection, in this example, COMPANY; and

(g') continues to a screen for sending a report, if sending a report is required, the functioning program method will, in this embodiment;

aid in composing the report;

aid in addressing the report;

send the report in an email format;

selecting connectivity as hardwired or wireless, depending on the connectivity selected in this particular embodiment, which may be variable, depending on the choices of hardware and software; alternatively

(i') when a user wants off-line training;

(j') data is inputted into the search function by the user, in this example,

ENGINE OUT;

(k') a list is presented with hyperlinked options, as discussed above

(l') the user selects an option;

(m') the selected option is outputted for study and review by the user.

[0046] The Electronic Kit Bag is conceived as a system that is not hardware, software, or component dependent, but rather conceptually and mechanically evolving, anticipating future incremental improvements, within the scope of the herein described purpose of the device, namely organizing, managing, manipulating, and outputting data, as well as integrating that data so that the device can be used as a portable interactive decision and support tool for flight operations, and even aircraft control. Accordingly, it is intended that this invention not be limited to these specific illustrative embodiments, but is to be interpreted within the full spirit and scope of the appended claims and their equivalents.

[0047] In summation, acknowledging that with the rapid advancement of technology, the precise hardware and software involved in this portable electronic flight system will evolve, but the integrity of the concept remains within the embodiment of the structure and methodology of this invention, and such variations are not to be regarded as a departure from the spirit and scope of the invention.

[0048] The foregoing description and accompanying drawings illustrate the principles, preferred embodiments and modes of operation of the invention. However, the invention should not be construed as being limited to the particular embodiments

discussed above. Additional variations of the embodiments discussed above will be appreciated by those skilled in the art.

[0049] Therefore, the above-described embodiments should be regarded as illustrative rather than restrictive. Accordingly, it should be appreciated that variations to those embodiments can be made by those skilled in the art without departing from the scope of the invention as defined by the following claims.